



SAFETY DATA SHEET

Sultraspot Tint (N)

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Sultraspot Tint (N)
Product number	7872/21486
UFI	UFI: PUSP-N04G-Y001-9A0F

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Spotting Agent
-----------------	----------------

1.3. Details of the supplier of the safety data sheet

Supplier	Christeyns NV Afrikalaan 182 9000 Gent Belgium Tel: +32 9 223 38 71 info@christeyns.be
Manufacturer	Cole & Wilson Ltd Rutland Street Bradford West Yorkshire BD4 7EA T:01274 393286 F: 01274 309143 info@colewilson.co.uk

1.4. Emergency telephone number

Emergency telephone	Christeyns NV: Tel: +32 9 223 38 71 (Mon-Fri 8am-4pm)
National emergency telephone number	(DE) Giftnotruf Berlin +49 30 19240 (24h erreichbar) (DE) Giftnotruf Berlin +49 (0)30 30686 790 (CH) STIZ, tel. 145 (CH) Centre suisse d'information toxicologique: +41.(0)1.251.51.51 (AT) Vergiftungsinformationszentrale: +43 1 40 400 2222 worldwide: http://www.who.int/ipcs/poisons/centre/directory/en (FR) CENTRE ANTI-POISON France: +33 45 42 59 59 ORFILA (INRS) (FR) CENTRE ANTI-POISON Nancy: +33 (03) 83 26 36 36 (FI) Myrkytystietokeskus +358 9 471 977 (BE) Belgisch Antigifcentrum/Centre Antipoisons Belge : +32 70 245 245 (ES) Teléfono Instituto Nacional de Toxicología: 915 620 420 (GB) NHS 111 (IT) Centro Antiveleni, Ospedale Niguarda Milano: +39 02 6610 1029 (CZ) Toxikologické informační středisko, Klinika pracovního lékařství VFN a 1. LF UK, Na Bojišti 1, 120 00 Praha 2: +420 224 919 293, +420 224 915 402 (SK) Národné toxikologické informačné centrum, Univerzitná nemocnica Bratislava, pracovisko Kramáre, Klinika pracovného lekárstva a toxikológie, Limbová 5, 833 05 Bratislava : +421 2 54 77 41 66 NHS Direct 111 (GB)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


Sultraspot Tint (N)

Classification (SI 2019 No. 720)

Physical hazards	Flam. Liq. 3 - H226
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word	Warning
Hazard statements	H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Contains	BUTYL ACETATE -norm
Detergent labelling	≥ 30% aliphatic hydrocarbons, 15 - < 30% anionic surfactants, 5 - < 15% aromatic hydrocarbons, < 5% soap

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BUTYL ACETATE -norm	30-50%
CAS number: 123-86-4	EC number: 204-658-1
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
(2-methoxymethylethoxy) propanol	30-50%
CAS number: 34590-94-8	EC number: 252-104-2
Classification	
Not Classified	
BENZENESULPHONIC ACID, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine	10-15%
CAS number: 84961-74-0	EC number: 284-664-9
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Aquatic Chronic 3 - H412	

Sultraspot Tint (N)

2-(Polyoxyethylene)propylheptamethyltrisiloxane CAS number: 67674-67-3	1-3%
Classification Acute Tox. 4 - H332 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if symptoms are severe or persist. Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Give milk instead of water if readily available. Get medical attention immediately.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapour from this product may be hazardous by inhalation. Vapours may irritate throat/respiratory system. Vapours may cause drowsiness and dizziness.
Ingestion	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	Causes skin irritation. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
Eye contact	This product is strongly irritating.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Powder. Foam. Alcohol-resistant foam. Carbon dioxide (CO ₂). Halon.
Unsuitable extinguishing media	Water.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable liquid and vapour. Heating may generate flammable vapours. Vapours may form explosive mixtures with air.
Hazardous combustion products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Flammable gases or vapours. Harmful gases or vapours. Oxides of the following substances: Carbon. Nitrogen. Sulphur.

5.3. Advice for firefighters

Sultraspot Tint (N)

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Dangerous for the environment if discharged into watercourses. Avoid discharge into drains or watercourses or onto the ground. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours. No smoking, sparks, flames or other sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Harmful to aquatic life with long lasting effects. Dangerous for the environment if discharged into watercourses. Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb in vermiculite, dry sand or earth and place into containers. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wash thoroughly after dealing with a spillage. Inform authorities if large amounts are involved. Dispose of contents/container in accordance with national regulations.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid contact with skin and eyes.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Take off immediately all contaminated clothing and wash it before reuse. Wash promptly with soap and water if skin becomes contaminated. Use appropriate hand lotion to prevent defatting and cracking of skin.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

Sultraspot Tint (N)

(2-methoxymethylethoxy) propanol

Long-term exposure limit (8-hour TWA): WEL 50 ppm 308 mg/m³

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

BUTYL ACETATE -norm (CAS: 123-86-4)

DNEL	<p>Consumer - Inhalation; Short term local effects: 859.7 mg/m³</p> <p>Consumer - Inhalation; Short term systemic effects: 859.7 mg/m³</p> <p>Workers - Inhalation; Short term systemic effects: 960 mg/m³</p> <p>Workers - Inhalation; Short term local effects: 960 mg/m³</p> <p>Consumer - Inhalation; Long term local effects: 102.34 mg/m³</p> <p>Workers - Inhalation; Long term local effects: 480 mg/m³</p> <p>Consumer - Inhalation; Long term systemic effects: 102.34 mg/m³</p> <p>Workers - Inhalation; Long term systemic effects: 480 mg/m³</p>
PNEC	<p>- Fresh water; 0.18 mg/l</p> <p>- Sediment (Freshwater); 0.981 mg/kg</p> <p>- Sediment (Marinewater); 0.981 mg/kg</p> <p>- marine water; 0.018 mg/l</p> <p>- STP; 35.6 mg/l</p> <p>- Soil; 0.0903 mg/kg</p>

(2-methoxymethylethoxy) propanol (CAS: 34590-94-8)

DNEL	<p>Workers - Dermal; Long term systemic effects: 283 mg/kg/day</p> <p>Consumer - Oral; Long term systemic effects: 36 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 37.2 mg/m³</p> <p>Consumer - Dermal; Long term systemic effects: 121 mg/kg/day</p> <p>Workers - Inhalation; Long term systemic effects: 308 mg/kg</p>
PNEC	<p>- STP; 4168 mg/l</p> <p>- Fresh water; 19 mg/l</p> <p>- Soil; 2.74 mg/kg/day</p> <p>- marine water; 1.9 mg/l</p> <p>- Sediment (Freshwater); 70.2 mg/kg/day</p> <p>- Intermittent release; 190 mg/l</p> <p>- Sediment (Marinewater); 7.02 mg/kg/day</p>

8.2. Exposure controls

Protective equipment



Appropriate engineering controls All handling should only take place in well-ventilated areas.

Eye/face protection Safety glasses with side-shields (EN 166).

Hand protection To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Polyethylene. Polyvinylidene chloride/polyethylene (PVDC/PE).

Other skin and body protection Wear suitable protective clothing (EN14605)

Hygiene measures Do not eat, drink or smoke when using this product.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Gas filter, type AX. Gas filter, type B. Gas filter, type E. Gas filter, type K.

SECTION 9: Physical and chemical properties

Sultraspot Tint (N)

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Yellow.
Odour	Characteristic.
pH	pH (concentrated solution): 7 - 8
Flash point	28°C
Relative density	0.89-0.95 @ 20°C
Solubility(ies)	No information available.

9.2. Other information

Other information	Not determined.
-------------------	-----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	The following materials may react with the product: Oxidising agents. Reducing agents. Alkalis.
------------	---

10.2. Chemical stability

Stability	Avoid the following conditions: Heat, sparks, flames. Contact with oxidisers and reducing agents. Avoid contact with alkalis. Avoid contact with flammable/combustible materials.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	The following materials may react with the product: Oxidising agents. Reducing agents.
------------------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Keep away from heat, sparks and open flame. Avoid contact with strong reducing agents. Avoid contact with strong oxidising agents.
---------------------	--

10.5. Incompatible materials

Materials to avoid	Strong alkalis. Strong oxidising agents. Strong reducing agents.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Flammable gases or vapours. Oxides of the following substances: Carbon. Nitrogen. Sulphur.
----------------------------------	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD ₅₀)	Based on available data the classification criteria are not met.
--------------------------------	--

Acute toxicity - dermal

Notes (dermal LD ₅₀)	Based on available data the classification criteria are not met.
----------------------------------	--

Acute toxicity - inhalation

Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
--------------------------------------	--

ATE inhalation (vapours mg/l)	550.0
-------------------------------	-------

Skin corrosion/irritation

Skin corrosion/irritation	Causes skin irritation.
---------------------------	-------------------------

Serious eye damage/irritation

Serious eye damage/irritation	Causes serious eye irritation.
-------------------------------	--------------------------------

Respiratory sensitisation

Respiratory sensitisation	Based on available data the classification criteria are not met.
---------------------------	--

Sultraspot Tint (N)

Skin sensitisation

Skin sensitisation May cause sensitisation or allergic reactions in sensitive individuals.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Gas or vapour is harmful on prolonged exposure or in high concentrations.

Ingestion

Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

Skin contact

Irritating to skin. Repeated exposure may cause skin dryness or cracking.

Eye contact

This product is strongly irritating. Symptoms following overexposure may include the following: Redness. Pain.

Acute and chronic health hazards

This product may cause skin and eye irritation. Repeated exposure may cause chronic eye irritation. Repeated exposure may cause chronic upper respiratory irritation. Mild dermatitis, allergic skin rash. Defatting, drying and cracking of skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Solvent vapours are hazardous and may cause nausea, sickness and headaches.

Route of exposure

Skin and/or eye contact
Ingestion.
Inhalation

Toxicological information on ingredients.

BUTYL ACETATE -norm

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ 23.4 vapours mg/l)

ATE inhalation (vapours mg/l) 23.4

(2-methoxymethylethoxy) propanol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 8,740.0 mg/kg)

Sultraspot Tint (N)

Species Rat

ATE oral (mg/kg) 8,740.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 9,510.0

Species Rabbit

ATE dermal (mg/kg) 9,510.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀
vapours mg/l) 3,404.47

Species Rat

ATE inhalation (vapours mg/l) 3,404.47

BENZENESULPHONIC ACID, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 2,001.0

Species Rat

ATE oral (mg/kg) 2,001.0

2-(Polyoxyethylene)propylheptamethyltrisiloxane

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

2,2',2"-NITRILOETHANOL

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

SECTION 12: Ecological information

Ecotoxicity Dangerous for the environment if discharged into watercourses. Harmful to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

BUTYL ACETATE -norm

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 18 mg/l, Pimephales promelas (Fat-head Minnow)
LC₅₀, 24 hours: 54 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 44 mg/l, Daphnia magna
LC₅₀, 24 hours: 24 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 647.7 mg/l, Scenedesmus subspicatus

Acute toxicity - microorganisms EC10, 16 hours: 115 mg/l, PSEUDOMONAS PUTIDA

Sultraspot Tint (N)

(2-methoxymethylethoxy) propanol

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: >1000 mg/l, Poecilia reticulata (Guppy)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 1919 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: >969 mg/l, Pseudokirchneriella subcapitata

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates	NOEC, 22 days: 0.5 mg/l, Daphnia magna LOEC, 22 days: 0.5 mg/l, Daphnia magna
--	--

BENZENESULPHONIC ACID, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 1.67-6.8 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 7.1 mg/l, Daphnia magna
Acute toxicity - aquatic plants	ECr50, 72 hours: 160 mg/l, Algae

2-(Polyoxyethylene)propylheptamethyltrisiloxane

Acute aquatic toxicity

Acute toxicity - fish	EC ₅₀ , 96 hours: 1-10 mg/l, Freshwater fish EC ₅₀ , 48 hours: 1-10 mg/l, Daphnia (water flea)
-----------------------	---

2,2',2"-NITRILOETHANOL

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 450-1000 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 1390 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 216 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in The Detergents Regulations (as amended).

Ecological information on ingredients.

(2-methoxymethylethoxy) propanol

Biodegradation - Degradation 75%: ~ 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Ecological information on ingredients.

(2-methoxymethylethoxy) propanol

Partition coefficient log Pow: ~ 0.006

12.4. Mobility in soil

Mobility The product is soluble in water and may spread in the aquatic environment

Ecological information on ingredients.

Sultraspot Tint (N)

(2-methoxymethylethoxy) propanol

Adsorption/desorption
coefficient

Water - Koc: ~ 0.28 @ °C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of in accordance with Local Authority regulations as special waste according to The Control of Special Waste Regulations 1996.

EURAL Code

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

UN No. (ADN) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (contains butyl acetate)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (contains butyl acetate)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (contains butyl acetate)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (contains butyl acetate)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

ADN packing group III

Sultraspot Tint (N)

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
Danish product registration number	PR4429569
Danish national regulations	Do not use by young people under 18 years of age In a workplace assessment, it must be ensured that employees are not exposed to influences that may involve a risk during pregnancy or breastfeeding (cf. the Danish Working Environment Authority's report on the work performance)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Revision comments	Revision is due to address change Revision is due to change of UFI number Revised classification.
Revision date	11/10/2022
Revision	13
Supersedes date	10/06/2021
SDS number	7872/21486
Hazard statements in full	H226 Flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.